

PREVO, A., kand.biol.nauk; SHAFROV, V.

Improving the taste of poultry. Mias. ind. SSSR 29 no.2:19 '58.

(MIRA 11:5)

1.Vsesoyuznyy nauchno-issledovatel'skiy institut ptitsepererabatyvayushchey promyshlennosti (for Prevo). 2.Bratsevsckaya ptitsofabrika (for Shatrov).

(Poultry)

SHAFROV, V.G.; TUROV, Ye.A.

Galvanomagnetic effects in ferrimagnetics near the compensation point. Zhur. eksp. i teor. fiz. 45 no.2:349-352 Ag '63.

(MIRA 16:9)

1. Institut fiziki metallov AN SSSR.

(Ferrimagnetism)

SH/FRAYONA, L.M.

Life-forms and morphogenesis of *Potentilla fruticosa* L. under
various conditions of growth. Biul. MOIP. Otd. biol. 69 no.4:
101-110 J1-Ag '64. (MIRA 17:11)

9(4)

PHASE I BOOK EXPLOITATION 30V/1778

Mashinotekhnicheskoye obshchestvo priborostroitel'noy promyshlennosti. Moskovskoye pravleniye
Transistorovaya elektronika v priborostroyeni, sbornik trudov konferentsii (Transistor Electronics in the Instrument-making Industry. Collection of Conference Transactions) Moscow, Gornost, 1959. 289 p. 1,400 copies printed.

Ed.: M.I. Gulyakov, Doctor of Technical Sciences, Professor; Ed. of Publishing House: S.D. Khametov; Tech Ed.: V.P. Koshin; Managing Ed.: A.S. Zaymovskiy, Engineer.

PURPOSE: The book is intended for scientific and engineering personnel of the instrument-making and radio industries engaged in the development of electronic and radio equipment.

COVERAGE: The authors of this collection of articles discuss the theory, principle of operation, calculation and application of electronic circuit using transistors. They also describe transistor application in measuring circuits, computers, radio and automatic and remote control circuits. The book is based on transactions of the Scientific and Engineering Conference organized by NTO in Moscow in December 1956. The conference discussed 54 papers on transistors, photocells, thermocouples, cooling elements, semiconductor capacitors, crystal diodes and transistors. A considerable number of these papers have been included in the present book. No personalities are mentioned. References appear at the end of each article.

TABLE OF CONTENTS:

A.A. Bektin, A.A. Petrovskiy, A. Ya. Mekrasovskiy, Engineers. New Relay for Signalling and Control
The authors discuss the construction and
Card 9/12

238

Operation of the MUV-2 electronic relay used in control systems of coal mines. The relay uses 207A-26 crystal diodes and P3A or P3V transistors. There are no references.

B.M. Mitrova, A.I. Pivovarov, Engineers. Experience in the Development of Photoelectric Relays Using Multi-conductors

The authors describe the construction and operation of P3-10 and P3-11 photoelectric relays using photoconductive-type triode transistors and discuss relay characteristics and constructional features. The relays were developed at the laboratory of Elektromekhanika. There are no references.

243

SHAFTAN, B. I.

Journal of Applied Chemistry
June 1954
Industrial Inorganic Chemistry

3
Mass production of cast steel parts. S. I. Bernshtein, V. R. Balinskii, and B. I. Shaftan (*Litovoe Proizvodstvo*, 1953, 3, No. 3, 2-5).—Problems involved in the mass production of corrosion-resisting steel castings for high-pressure work are considered. The steel used contained Mn 1.5, Cr 17-19, Ni 8-9.5, and Ti 0.8%. Special attention is devoted to variations in Si and Ti contents during acid melting and casting. Mechanical properties of cast specimens of different shapes are compared, and the influence of Ti on these properties is illustrated. Results of corrosion and intercryst. corrosion tests on cast specimens show the decisive influence of Ti. J. IRON STEEL INST. (R.B.C.).

VINOKUR, D.Ya.; SHAFTAN, R.B.

Improve the selection of silk fabrics. Tekst. prer. 19 no.5:77-79

My '59.

(MIRA 12:10)

(Textile fabrics) (Synthetic fabrics)

VINOKUR, D.Ya.; SHAFTAN, R.B.

Improving the selection and quality of staple fiber fabrics.
Tekst. prom. 19 no.6:75-76 Je '59. (MIRA 12:9)
(Textile fabrics)

S/056/60/039/005/007/051
B029/B077

AUTHORS: Vasil'yev, S. S., Shaftvalov, L. Ya.

TITLE: The β^+ Spectrum of Si^{27}

PERIODICAL: Zhurnal eksperimental'noy i teoreticheskoy fiziki, 1960,
Vol. 39, No. 5(11), pp. 1221 - 1223

TEXT: The authors investigated the β^+ spectrum of Si^{27} using a β -spectrometer with a magnetic lens. Si^{27} was obtained by the reaction $\text{Al}^{27}(\text{p}, \text{n})\text{Si}^{27}$ in the 120-cm cyclotron of NIIYaF MGU (Scientific Research Institute of Nuclear Physics, Moscow State University). The proton beam emitted by the cyclotron was focused by quadrupole lenses and hit the target which was placed 9 m away from the cyclotron behind a concrete shield. Before hitting the target the protons passed through a screen connected to an integrator. The aluminum target consisted of a 2.7 mg/cm^2 thick rotating ring. This arrangement brought the irradiated parts of the target into the focus of the β -spectrometer, and using a

Card 1/3

The β^+ Spectrum of Si^{27}

S/056/60/039/005/007/051
B029/B077

suitable rotation velocity it was possible to move the radioisotopes into the focus of the β -spectrometer with the wanted half-life. A strong background complicated the measurements considerably. The Fermi chart shows that the β^+ spectrum of Si^{27} consists of two partial spectra. The upper limit of the fundamental β^+ spectrum is 3.65 ± 0.05 Mev, and its relative intensity is $\sim 90\%$. The upper limit of the weaker β^+ spectrum is 1.45 ± 0.1 Mev, and its relative intensity is $< 10\%$. The decay scheme found in the book of B. S. Dzhelepov and L. K. Peker (Ref.5) yields a level of 2270 kev in Al if a partial β^+ spectrum with an upper limit of 1.45 ± 0.1 Mev is added. This level is observed when investigating inelastic scattering. It has a positive parity and a $5/2$ spin like the ground state of the Si^{27} nucleus. Therefore, the β -transition that leads to this level is more probable than transitions leading to other states of Al^{27} . The half-life of Si^{27} was calculated to be 4.1 ± 0.4 sec and agrees with the known value within the limits of error. Finally, the method of half-life determination is briefly described. The authors thank the cyclotron team and

Card 2/3

The β^+ Spectrum of Si^{27}

S/056/60/039/005/007/051
B029/B077

especially Yu. A. Vorob'yev, Z. I. Tikhomirova, B. M. Makuni, and N. S. Kirpichev for their cooperation, and also B. S. Zazulin for calculating the half-life. There are 3 figures and 6 references: 2 Soviet, 3 US, and 1 Canadian.

ASSOCIATION: Institut yadernoy fiziki Moskovskogo gosudarstvennogo universiteta (Institute of Nuclear Physics, Moscow State University)

SUBMITTED: June 23, 1960

Card 3/3

3114500-1100/110
MERLIN, V.S.; MARTYNOV, D.Ya., otvetstvennyy redaktor; MARKOV, M.V., professor, redaktor; SHAFUGULLIN, A.G., professor, redaktor; ARBUZOV, B.A., professor, redaktor; DYUKOV, I.A., professor, redaktor; NORDEN, A.G., professor, redaktor; PISAREV, V.I., professor, redaktor; TIKHVINSKAYA, Ye. I., professor, redaktor; ABDRAKHMANOV, M.I., dotsent, redaktor; MOROZOV, D.G., dotsent, redaktor; KHARITONOV, A.P., dotsent, redaktor; KOLOBOV, N.V., redaktor; KOLESNIKOVA, Ye.A., starshiy prepodavatel', redaktor; ROZHDESTVENSKIY, B.P., dotsent, redaktor.

[Peculiarity of conditioned reactions in the structure of a voluntary act] Svoebrazie uslovykh reaktsii v strukture volevogo akta. Kazan', 1953. 123 p. (Kazan. Universitet. Uchenye zapiski, vol.113, no.3)

(MIRA 10:3)

1. Rektor universiteta (for Martynov); 2. Proroktor po nauchnoy rabote (for Markov); 3. Proroktor po uchebnoy rabote (for Shafugullin); 4. Sekretar' partbyuro universiteta (for Kolobov)
- (CONDITIONED RESPONSE) (WILL)

MADANOV, P.V.; MARTYNOV, D.Ya., otvetstvennyy redaktor; MARKOV, M.V., professor, redaktor; SHAFUGULLIN, A.G., professor, redaktor; ARBUZOV, B.A., akademik, redaktor; DYUKOV, I.A., professor, redaktor; NORDEN, A.P., professor, redaktor; PISAREV, V.I., professor, redaktor; TIKHVINSKAYA, Ye.I., professor, redaktor; ABDRAKHMANOV, M.I., dotsent, redaktor; MOROZOV, D.G., dotsent, redaktor; KHARITONOV, A.P., dotsent, redaktor; KOLOBOV, N.V., redaktor; KOLESHNIKOVA, Ye.A., starshiy prepodavatel', redaktor; VINOKUROV, M.A., professor, redaktor.

[Biological accumulation of manganese in soils of the Volga-Kama forest-steppe and its availability to plants] Biologicheskaya akumulatsiya margantsa v pochvakh Volzhsk-Kamskoi lesostepi i ego dostupnost' sel'skokhoziaistvennym rasteniyam. Kazan', 1953. 202 p. (Kazan. Universitet. Uchenye zapiski, vol.113, no.7) (MIRA 10:3)

1. Rektor universiteta (for Martynov). 2. Prerektor po nauchnoy rabote (for Markov). 3. Prerektor po uchebnoy rabote (for Shafugullin)
 4. Sekretar' partbyuro universiteta (for Koleshev).
- (Plants, Effect of manganese on)
(Volga Valley--Forest soils)

SHUSHUMOV, T. A., SHUSHUMOV, A. I.

Calcium Hydride

Kinetics of formation of calcium hydride. Zhur. fiz. khim., 26, No. 5, 1952.

Monthly List of Russian Accessions, Library of Congress, November 1952. Unclassified.

SHAG, I. F.

Shag, I. F. -- "Application of the Artanov System of Automatic Levelling Instruments for Railroad Surveys." Min Transport Building USSR, All-Union Sci Res Inst of Railroad Construction and Planning, Moscow, 1955 (Dissertation for the Degree of Candidate in Technical Sciences)

SO: Knizhnaya Letopis', No. 23, Moscow, Jun 55, pp 87-104

SHAGA, V.S.

Young naturalists study the nature of their homeland. Biol. v
shkole no.4:61-62 J1-Ag '63. (MIRA 16:9)

1. Vos'miletnyaya shkola No.44, Khabarovsk.
(Khabarovsk Territory--Nature study)

SHAGA, V.S.

New floral finds in the central Sikhote-Alin' Range.

Bot.zhur. 50 no.11:1623-1625 N '65.

(MIRA 19:1)

1. Dal'nevostochnyy nauchno-issledovatel'skiy institut
lesnogo khozyaystva, Khabarovsk. Submitted March 25, 1964.

DIOMIDOV, A. P., dotsent; MELKIKH, V. I., inzh.; VOLEGOV, A. V., inzh.;
SHAGABUTDINOV, G. N., starshiy prepodavatel'

Estimation of the work efficiency of drum screens employed in
classifying asbestos concentrates. Izv. vys. ucheb. zav.;
gor. zhur. 5 no.8:169-175 '62. (MIRA 15:10)

1. Sverdlovskiy gornyy institut imeni Vakhrusheva. Rekomendovana
kafedroy obogashcheniya poleznykh iskopayemykh.

(Screens(Mining)) (Asbestos)

SKORODUMOV, V.A.; SHAGAKO, N.K.; ZHURAVLEV, S.V.

Synthesis in the phenothiazine series. Part 13: Selective reduction of
10-methyl-3-nitro-5-oxidophenothiazine. Zhur.ob.khim. 34 no.2:621-623
F '64. (MIRA 17:3)

MATLINA, E.A.; SHAGAL, D.I. (Moskva)

Effect of ACTH on adrenaline and noradrenaline excretion in
the urine in myopathy. Probl. endok. i gorm. 9 no.5:66-70
S-O '63 (MIRA 16:12)

1. Iz laboratorii neyro-gumoral'noy regulyatsii (zav. - chlen-
korrespondent AN SSSR N.I.Grashchenkov, rukovoditel' problemy
prof. G.N.Kassil') Instituta vysshey nervnoy deyatel'nosti i
neyrofiziologii AN SSSR.

IL'INA, N.A.; SHAGAL, D.I.

Diencephalic disorders in myopathy. Zhur. nevr. i psikh. 63
no.8:1133-1138 '63. (MIRA 17:10)

1. Klinika nervnykh bolezney (zav. - prof. V.V. Mikheyev) i
Moskovskogo ordena Lenina meditsinskogo instituta i laboratoriya
neyro-gumoral'noy regulyatsii (zav. - chlen-korrespondent AN SSSR
N.I. Grashchenkov) Instituta vysshey nervnoy deyatel'nosti i neyro-
fiziologii AN SSSR, Moskva.

L 25167-65

ACCESSION NR: AP5005772

S/0219/64/058/010/0003/0008

AUTHOR: Pratushevich, Yu. M.; Shagal, D. I.

TITLE: Dynamics of reactive potentials of the brain and biologically active substances of the blood in children subjected to cold

SOURCE: Byulleten' eksperimental'noy biologii i meditsiny, v. 58, no. 10, 1964, 3-8

TOPIC TAGS: human physiology, blood, nervous system

Abstract: The dynamics of the electrical reactivity of the brain and biologically active substances in the blood of 13-15 year-olds was studied in combination with the reflex effect of a cold stimulus on the skin receptor for one minute. The cold stimulus caused some decline in the synchronization coefficient and a greater decline in the reactive potentials for various regions of the spectrum. The children showed a greater instability in the content of adrenaline-like substances and a higher acetylcholine content than adults. The acetylcholine content increases with the effect of cold in the children, whereas it drops in adults. Orig. art. has 2 figures and 1 table.

Card 1/2

L 25167-65

ACCESSION NR: AP5005772

ASSOCIATION: Laboratoriya neuro-gumoral'noy regulyatsii Instituta vysshey
nervnoy deyatel'nosti i neyrofiziologii AN SSSR, Moscow (Laboratory of Neuro-
Humoral Regulation, of the Institute of Higher Nervous Activity and Neurophysiology,
AN SSSR)

SUBMITTED: 23Jul63

ENCL: 00

SUB CODE: LS

NO REF SOV: 016

OTHER: 006

JPRS

Card 2/2

SHAGAL, D.I.; SHRAYBERG, G.L.

Functional state of the adrenal cortex in myopathies. Probl. endok.
i gorm. 10 no.1:9-15 Ja-F '64.

(MIRA 17:10)

1. Laboratoriya neyro-gumoral'noy regulyatsii (zav. - chlen-korrespondent AN SSSR prof. N.I. Grashchenko) AN SSSR (rukovoditel' raboty - prof. G.N. Kassil').

KASSIL', G.N.; GRIGOR'YEV, M.Ya.; CHREYBERG, G.L.; VAYSELD', L.L.;
RAYT, M.L.; SHAGAL, D.I.

Humoral mechanisms of reactions caused by the introduction
of carbocholine into cerebrospinal fluid. Dokl. AN SSSR
156 no. 1:544-567 1964. (MIRA 1786)

1. Predstavleno akademikom V.N.Chernigovskim.

PRATUSEVICH, Yu.M.; SHAGAL, D.I.

Dynamics of the reactive potentials of the brain and biologically active substances in the blood under the effect of cold in children. Biul.eksp.biol.i med. 58 no.10:3-8 0 '64.

(MIRA 18:12)

1. Akademicheskaya gruppa pri deystvitel'nom chlene AMN SSSR prof. G.M.Speranskom i laboratoriya neyro-gumoral'noy regulyatsii (zav. - deystvitel'nyy chlen AMN SSSR prof. N.I.Grashechenkov) Instituta vysshey nervnoy deyatel'nosti i neyrofiziologii AN SSSR, Moskva. Submitted July 23, 1963.

GLUKHOVSKIY, K.; IVOYLOV, A.; SHAGAL, G.

Thin-walled reinforced concrete three-dimensional shells. Na
stroitel'stvo. no.1:10-13 Ja '61. (MIRA 14:6)

1. Zamestitel' nachal'nika Glavleningradstroya (for Glukhovskiy). 2.
Direktor proyektного instituta No.1 Ministerstva stroitel'stva
RSFSR (for Ivoylov). 3. Glavnyy konstruktor proyektного
instituta No.1 Ministerstva stroitel'stva RSFSR (for Shagal).
(Roofs, Shell) (Reinforced concrete construction)

SHMYKOV, P.A., inzhener; SHAGAL, G.M., inzhener; GOGIN, Ya.I., inzhener;
MALKOV, D.E., inzhener.

Precast prestressed reinforced shell arches. Nov.tekh.i pered.op.
v stroi. 18 no.12:9-12 D '56. (MLRA 10:1)
(Roofs, Shell) (Prestressed concrete construction)

SOV/124-57-8-9613

Translation from: Referativnyy zhurnal. Mekhanika, 1957, Nr 8, p 145 (USSR)

AUTHOR: Shagal, G. M.

TITLE: Prefabricated Double-bent Shells of Reinforced Concrete (Sbornyye zhelezobetonnyye obolochki dvoyakoy krivizny)

PERIODICAL: V sb.: 15-ya nauchn. konferentsiya Leningr. inzh.-stroit. in-ta, Leningrad, 1957, pp 60-62

ABSTRACT: Bibliographic entry

Card 1/1

GLUKOVSKIY, K.A.; IVOYLOV, A.A.; LOBANOV, N.D.; SHAGAL, N.D.; EMDIN, N.A.

Precast prestressed reinforced concrete shells for covering industrial and public buildings. Prom. stroi. 39 no.3:30-35 '61.

(MIRA 14:4)

(Precast concrete construction)

(Roofs, Shell)

BODYANSKIY, Vadim Lazarevich; SHAGAL', Vladimir Eduardovich;
LEBEDEV, Ye.A., otv. red.; DEKUR, I.M., red.

[Modern Libya; a reference book] Sovremennaya Libiya;
spravochnik. Moskva, Nauka, 1965. 300 p.
(MIRA 19:1)

SHAGALEV, L.B.

7
 γ -(3-indolyl)butyrate. N. M. Surov, V. P. Mamayev,
 and L. B. Shagalev. U.S.S.R. 105,124, Mar. 25, 1967.
 Addn. to U.S.S.R. 95,779. The cyclization of $\text{PhNHN} \cdot$
 $\text{CH}(\text{CH}_3)\text{CO}_2\text{Et}$ is carried out with H_2PO_4 in boiling Cello-
 solve. This procedure simplifies the process and increases
 the yield. M. Hosh

PM
 MIT

SHAGALIN, A.N., inzh.

Hydraulic switch. Ved. 1 san. tekhn. no. 3334 '64 (MIRA 1832)

SHAGALIN, M.N., inzh.

Boring with electric core drills with a constant axial pressure.
Ugol' Ukr. 10 no. 1:50 Ja '66. (MIRA 18:12)

1. Konotopskiy institut Avtomatuglerudprom.

SOV/165-58-6-18/24

AUTHOR: Shagalin, S.F.

TITLE: The Effect of a Single Dosage of the Spores of the Toadstool
Arthrobotrys Oligospora Fres. Upon the Number of Nematode Larvae
in the Feces of Sheep

PERIODICAL: Izvestiya Akademii nauk Turkmenskoy SSR, 1958, Nr 6, pp 105-107
(USSR)

ABSTRACT: The single dosage of a preparation with spores of the toadstool
Arthrobotrys Oligospora Fres., given to a group of sheep in the
amount of 400 g per animal, led to the lessening of the number of
larvae in the feces of, on the average, 1.9 times in six days, to
8 times on individual days, and to the complete disappearance of
them. The number of these larvae remains at a low level during
the 11 days after the dosage is given. The taking of the prepara-
tion has, in no way, a disadvantageous effect upon the organism
of the animals.

Card 1/2

SOV/165-58-6-18/24

The Effect of a Single Dosage of the Spores of the Toadstool *Arthrobotrys Oligospora* Fres. Upon the Number of Nematod Larvae in the Feces of Sheep

There are 1 table and 2 Soviet references.

ASSOCIATION: Institut zoologii i parazitologii AN Turkmenkoy SSR (Institute of Zoology and Parasitology of AS of the Turkmenian SSR)

SUBMITTED: April 9, 1958

Card 2/2

SHAGALIN, S. F. Cand Vet Sci -- "Predatory fungi in the ~~prophylaxis~~ of strongylosis in horses and sheep under conditions of Turkmenistan." Ashkhabad, 1960 (State Committee of Higher and Secondary Specialized Education of the Council of Ministers Turkmen SSR. Turkmen Agr Inst im M. I. Kalinin). (KL, 1-61, 204)

SHAGALIN, Ya.

Progressive base. Sov. torg. 35 no.8:25-23 Ag '62.
(MIRA 15:8)
(Moscow--Wholesale trade)

TENDETNIK, Yu.Ya.; SONIN, M.D.; SHAGALINA, L.M.

Studying helminths of wild birds of southern Turkmenistan. Izv.
AN Turk. SSR. Ser. biol. nauk no.6:78-85 '61. (MIRA 15:1)
(TURKMENISTAN PARASITES--BIRDS)
(WORMS, INTESTINAL AND PARASITIC)

SHAGALINA, L.M.

Methods for preparing preparations predatory fungi and
selecting active strains. Izv. AN Turk. SSR. Ser. biol.
nauk no.1:42-47 '62. (MIRA 15:3)

1. Institut zoologii i parazitologii AN Turkmenskoy SSR.
(FUNGI, PREDATORY)

SHAGALOV, A.F.; MIKERIN, B.I.; POKHITUN, L.Ye.

Causes of explosions in the crankcases of 96K gas-engine compressors. Neftteper. i neftekhim. no.4:39-42 '65.

(MIRA 18:5)

L 27947-66

ACC NR: AP6017709

SOURCE CODE: UR/0105/66/000/001/0086/0086

AUTHOR: Avilov-Karnaukhov, B. N.; Bol'sham, Ya. M.; Venikov, V. A.; Volobrinskiy, S. D.; Yermilov, A. A.; Konstantinov, B. A.; Knyazevskiy, B. Ye.; Minin, G. P.; Miller, G. R.; Mukoseyev, Yu. I.; Petrov, I. I.; Serbinovskiy, G. V.; Syromyatnikov, I. A.; Fedorov, A. A.; Kholmkiy, G. V.; Shagalov, A. S.; Chilikin, M. G.

ORG: none

TITLE: Prof. Georgiy Mikhaylovich Kayalov (on his 60th birthday)

SOURCE: Elektrichestvo, no. 1, 1966, 86

TOPIC TAGS: academic personnel, electric engineering personnel, electric equipment

ABSTRACT: In 1929, G. M. Kayalov completed the electrotechnical department of the Mechanical Faculty of the Novocherkassk Polytechnical Institute. Until 1947, he worked in the planning department of the Rostov Division of the All-Union Electrotechnical Union. In this time, he rose to the position of Chief Engineer. He directed the planning of a large number of important pieces of electrical equipment for various projects. He was active in the postwar restoration of many important industrial enterprises. He is the author of almost 70 published works, and has made a great contribution to modern, scientifically based methods of design and analysis of electrical loads for industrial equipment. He is on a number of commissions and in many scientific and technical societies. Orig. art. has: 1 figure. [JPRS]

SUB CODE: 09 / SUBM DATE: none

Card 1/1 B.L.G.

UDC: 621.34

SHAGALOV, D.A.

Manufacture of multilayer skis using birch plywood. Der. prom.
13 no.8:20-21 Ag '64. (MIRA 17:11)

MAKALOV, Dmitriy Artem'yevich; SMOLENSKIY, K.I., red.

[Manufacture of glued bentwood furniture parts; experience of the enterprises in Vologda Province] Proizvodstvo gnutokleennykh detalei mebeli; opyt predpriyatii Vologodskoi oblasti. Moskva, Izd-vo "Lesnaya promyshlennost'," 1964. 35 p. (MIRA 17:7)

BALEK, A.; GABESAM, L., inzh.; KHAVELKOVA, B., inzh.; STITSKEL, I., inzh.;
SHVAGR, Ya., inzh.; TITERA, D., inzh. ZHDYARSKIY, M., doktor;
SEME NOV, I.I. [translator]; KORMNOV, Yu.F., red.; SHAGALOV, G.L.,
red.; REZOUKHOVA, A.G., tekhn.red.

[Economic development of Czechoslovakia from 1948 through 1958]
Ekonomicheskoe razvitie Chekhoslovakii, 1948-1958 gg. Red.IU.F.
Kormnov. Moskva, Izd-vo inostr.lit-ry, 1959. 367 p. Translated
from the Czech. (MIRA 13:4)

1. Gosudarstvennoye statisticheskoye upravleniye Chekhoslovakii
(for Balek, Gabesam, Khavelkova, Stitskel, Shvagr, Titera, Zhdyarskiy).
(Czechoslovakia--Economic conditions)

KARPINSKIY, A. [Karpinski, Andrzej]; RAKOVSKIY, M. [Rakowski, Mieczyslaw];
SOKOLOVSKIY, V.I. [translator]; SHALASHOVA, V.P. [translator]; MA-
KARENKO, Ya.I., red.; SHAGALOV, G. [red.]; KHOMYAKOV, A.D., tekhn.
red.

[Poland against the background of the world economy] Pol'sha na fone
mirovoi ekonomiki. Pod obshchei red. IA.I. Makarenko. Moskva, Izd-vo
inostr. lit-ry, 1961. 221 p. Translated From the Polish. (MIRA 14:11)
(Poland—Economic conditions) (Economic conditions)

RAMZES, V.B. [translator]; RUSETSKIY, S.B. [translator]; PEVZNER, Ya.A.,
red.; SHAGALOV, G.L., red.; DZHATIYEVA, F., tekhn. red.

[Monopolistic capital of modern Japan. Translated from the Japanese]
Monopolisticheskii kapital sovremennoi Iaponii. Moskva, Izd-vo ino-
str. lit-ry, 1961. 322 p. (MIRA 14:7)
(Japan--Capital) (Japan--Trusts, Industrial)

SHAGALOV, G. (L.)

Methods of determining the economic effectiveness of foreign
trade in Poland. Vnesh. torg. 42 no.3:18-23 '62. (MIRA 15:3)
(Poland--Commerce)

KHACHATUROV, T.S., red.; DAN'SHINA, V.N.[translator]; ZOTOV, B.D.
[translator]; ISUPOV, V.T.[translator]; MENIKER, V.D.[translator];
TEREKHOV, V.F.[translator]; SHAGALOV, G.L.[translator]; KORMNOV,
Yu.F., nauchnyy red.; ZAYTSEV, N.F., red.; KHOMYAKOV, A.D., tekhn.
red.

[Problems in the economic efficiency of capital investments] Vopro-
sy ekonomicheskoi effektivnosti kapitalovlozhenii; sbornik statei.
Pod red. i so vstup. stat'ei T.S.Khachaturova. Moskva, Izd-vo
inostr. lit-ry, 1962. 276 p. (MIRA 15:12)

1. Chlen-korrespondent Akademii nauk SSSR (for Khachaturov).
(Capital investments)

SHARON, I. V.

Chem Abs

V-48 25 Jan 54

Organic Chem

Diethyl 1,2,3,4-tetrahydro-1-oxo-2-phenyl-3,3-naphthalenedicarboxylate. V. M. Rodionov, N. N. Shvartov, and L. V. Smagolov. *Akad. Nauk S.S.S.R., Inst. Org. Khim., Sotsey Org. Soedinenii, Sbornik* 2, 94-7 (1952); cf. *C.A.* 44, 2504c. To 150 ml. abs. EtOH is added 6.75 g. sliced Na and the resulting hot soln. is treated slowly with 73.5 g. $\text{PhCH}_2\text{CH}(\text{CO}_2\text{Et})_2$. The mixt. is refluxed on oil bath while 75 g. $\text{PhCHBrCO}_2\text{Et}$ is added to it dropwise and the refluxing with stirring is continued 15 hrs. until the mixt. is no longer alk. to litmus. EtOH is distd. and the residue dild. with 50 ml. H_2O and 100 ml. satd. aq. NaCl. After stirring to dissolve NaBr ppt., the mixt. is extd. with Et_2O (filtration may be necessary to break emulsions) and the aq. layer is extd. twice with Et_2O . The combined exts. yield an unstated amt. of $\text{PhCH}_2\text{C}(\text{CO}_2\text{Et})_2\text{CHPhCO}_2\text{Et}$, b_p about 200°, m. 46-7°. To 6 g. of this ester is added 15 ml. 92% H_2SO_4 and the mixt. allowed to stand 14 days in closed vessel; after pouring on ice the mixt. is extd. with Et_2O , the ext. is washed with satd. NaCl soln., followed by 10% Na_2CO_3 (1-1.5 l. Et_2O is needed), again with satd. NaCl, dried and coned, yielding 40-5% di-Et 1,2,3,4-tetrahydro-1-oxo-2-phenyl-3,3-naphthalenedicarboxylate, m. 117-18°, after washing with petr. ether and cold EtOH. Hydrolysis with aq. alc. NaOH yields the dicarboxylic acid, m. 142-2.5°.

G. M. Kosolapoff

③ 4

1. K. m

MT

CHAUHLO / L J

Perm

Phen Abs

V-48 25 Jan 54

Organic Chem

~~1,2,3,4-Tetrahydro-1-oxo-2-phenyl-3-naphthalenecarboxylic acid.~~ V. M. Rodionov, N. N. Suvorov, and L. V. Sharalov. *Akad. Nauk S.S.S.R., Inst. Org. Khim., Sintezy Org. Soedinenii, Sbornik 2*, 138-9 (1952).—Di-Et 1,2,3,4-tetrahydro-1-oxo-2-phenyl-3,3'-naphthalenedicarboxylate (I) (5 g.) is refluxed with 50 ml. 10% NaOH and 20 ml. EtOH 2 hrs.; EtOH is distd. and the residue dild. with H₂O and filtered. The filtrate acidified with HCl to Congo red yields a ppt. of the free dicarboxylic acid. This heated at 150-60°, until CO₂ evolution stops, gives little compd. (II), isolated by soln. of the residue in 20 ml. hot MePh and addn. of 10 ml. hot heptane. The acid is obtained in 66% yield, m. 139-41° [pure, m. 142-3° (from MePh)]. The crude product is directly used below. The product formed from 2.85 g. (I) is refluxed 4 hrs. with 30 ml. abs. EtOH and 1.2 ml. concd. H₂SO₄; after cooling with ice there is formed 1.4 g. II *Et ester* (III), m. 89-9.5°; 0.35 g. can be obtained by concn. of the residual soln. After washing with cold EtOH there is obtained 81% yield III, m. 90-1° (from EtOH) (cf. C.A. 44, 2604e). G. M. K.

7-14-54

SHAGALOV L. V.

USSR/Chemistry - Pharmaceuticals Alkaloids

Feb 52

"Synthesis of 6-Carboxy-11methyl-5, 6, 13, 14- tetrahydro-1, 2-benzophenanthridine (I)," Acad V. M. Rodionov, N. N. Suvorov, and L. V. Shagalov

"Dan SSSR" Vol 82, No 5, pp 731 - 734

(I) was synthesized with a theoretical yield of 75%. It has a structure similar to that of the alkaloid helidonine.

238T2

Shagalov, L. B.

Synthesis of halogen-substituted γ -(3-indolyl)butyric acids. N. N. Suvorov, Y. P. Mamaev, and L. B. Shagalov. Doklady Akad. Nauk S.S.S.R. 93, 837-8 (1967).
 5 g. p -FC₆H₄NH₂ and 6 g. $\text{OHCCH}_2\text{CH}_2\text{CH}_2\text{CO}_2\text{H}$ in 20 ml. EtOH 0.5 hr., aq. soln. of CaH₂, evapn. of the sol-
 vents *in vacuo* and refluxing the residue with 4 ml. concd. H₂SO₄ in 45 ml. abs. EtOH 10 hrs. gave after addn. of ice and extrn. with Et₂O, 28.5% Et γ -[3-(5-fluorindolyl)]butyrate, m. 68.5-9.5°; this refluxed 15 min. in 5% alc. KOH gave 100% free acid, m. 121-3° (from MePh). Similarly p -ClC₆H₄NH₂ gave 27% Et γ -[3-(5-chlorindolyl)]butyrate, m. 67-8° (from heptane), which gave 100% free acid, m. 139.5-40° (from MePh). p -BrC₆H₄NH₂, similarly gave 9.7% Et γ -[3-(3-bromindolyl)]butyrate, m. 70.5-7.1° (from heptane), which gave 100% free acid, m. 146-7° (from MePh). Similarly was obtained 6.1% Et γ -[3-(5-iodindolyl)]butyrate, m. 83-7.5° (from C₆H₆-heptane), yielding 100% free acid, m. 154.5-5.5° (from MePh). The reaction of m -ClC₆H₄NH₂ gave 24% mixed Et γ -[3-(4-chloro- and 6-chlorindolyl)]butyrate, b.p. 203-24°, m. 55-7°, which were sepd. by chromatographic adsorption on Al₂O₃ from C₆H₆ and elution with the same solvent, yielding the 2 isomers, m. 82-3° and 68-9°; the identity of each is unknown. Hydrolysis gave the free acids, m. 145-6.5° and 135.5-7.0°. Hydrolysis of the mixed esters gave the mixed free acids, m. 121-2°. o -ClC₆H₄NH₂ similarly gave 18.6% Et γ -[3-(7-chlorindolyl)]butyrate, m. 63.5-4.5°, which gave the free acid, m. 137-7.5° (from MePh-heptane).
 G. M. Kosolapoff

SHAGALOV, L.B.

Synthesis of 5-alkoxy- and 5-aryloxy- γ -3-indolylbutyric acids. N. N. Savitsky, V. P. Abramov, and L. B. Shagalov (L. I. Mendeleev Chem. Technol. Inst., Moscow; Dokl. Akad. Nauk S.S.S.R. 101, 103-4 (1965); cf. C.A. 49, 10064). — Diazotization of p -H₂NC₆H₄OPh in HCl and reduction at -5° with SnCl₄·HCl yielded, after treatment of the product with 25% NaOH 1 hr., 54% p -PhOC₆H₄NHNH₂ (I), m. 86-7° (from petr. ether); HCl salt, decomp. 182-3° (from H₂O). 2,4-Cl₂(MeO)C₆H₃NH₂ similarly gave 29% unstable 2,4-Cl₂(MeO)C₆H₃NHNH₂ (II), m. 59-9.5°. Refluxing 7.5 g. p -MeOC₆H₄NHNH₂ and 8.6 g. Et 3-formylvalerate in EtOH 0.5 hr., followed by addn. of C₆H₆, removal of solvents *in vacuo* and refluxing the residue with 15 g. H₃PO₄ and 200 ml. MeOH 8.5 hrs., followed by diln. with H₂O, gave 50.3% Et γ -[3-(5-methoxyindolyl)]butyrate, m. 70.5-1.5° (from aq. EtOH); this hydrolyzed with 5% alc. KOH to 92% free acid (III), m. 135-5.5° (from H₂O or C₆H₆). Similarly p -PhCH₂OC₆H₄NHNH₂ and Et 3-formylvalerate in EtOH gave after the above treatment, followed by hydrolysis of the crude ester with 5% alc. KOH γ -(5-benzylindolyl)butyric acid, m. 161.5-2.5° (from EtOH). I similarly gave 29% γ -[3-(5-phenoxindolyl)]butyric acid, m. 107-8° (from aq. EtOH), while II gave 31% γ -[3-(5-methoxy-7-chloroindolyl)]butyric acid, m. 133.5-6.6° (from MeOH). All had low growth stimulating activity except III which was close to γ -3-indolylbutyric acid.

G. M. Kosolapoff

(2)

ZASOSOV, V.A.; METEL'KOVA, Ye.I.; VOLZHINA, O.N.; SHAGALOV, L.B.; VLASOV,
A.S.

New method of producing norsulfazole. Med. prom. 17 no.9:15-22
S'63. (MIRA 17:5)

1. Vsesoyuznyy nauchno-issledovatel'skiy khimiko-farmatsevticheskiy
institut imeni Sergo Ordzhonikidze.

SHAGALOV, L.B.; SOROKINA, N.P.; SUVOROV, N.N.

Derivatives of indole. Part 21: Synthesis of
4- and 6-chloroindolylbutyric acids. Zhur. ob. khim. 34
no. 5:1592-1595 My '64. (MIRA 17:7)

1. Vsesoyuznyy nauchno-issledovatel'skiy khimiko-farmatsevticheskiy
institut imeni Ordzhonikidze.

EXCERPTA MEDICA Sec 13 Vol 13/8 Dermatology Aug 59

2264. SYNTHOMYCIN THERAPY FOR GONORRHOEA (Russian text) - Shagalov
M. N. Turkmen Dermato-Vener. Res. Inst., Ashkhabad - TRUDY TURKM.
KOZHNO-ENER. INST. (Ashkhabad) 1957, 5 (246-252)
Synthomycin (chloramphenicol), administered perorally for 3-4 days (total dosage
10-15 g.) cured gonorrhoea in 50 out of 51 men (46 had acute and 5 ascending
gonorrhoea) and all of 17 women treated (chronic form in 10 cases, acute form in
6 patients and ascending form in one case). References 11.

Mashkilleison Jr - Moscow (S)

PROSHIN, Anatoliy Sergeyevich; ZBOROVSKAYA, R.L., inzh., red.; SHAGALOV, Ye.S., red.; VELITSYN, B.L., tekhn. red.

[Mechanization of the basic assembly operations in the construction of high-capacity thermal electric power plants] Mekhanizatsiya osnovnykh montazhnykh rabot pri stroitel'stve moshchnykh teplovykh elektrostantsii. Moskva, Orgenergostroi, 1960. 62 p.

(MIRA 14:11)

(Electric power plants--Design and construction)
(Hoisting machinery)

BAKHMETOVA, T.Ye.; DOVGER, F.F.[deceased]; SMIRNOV, P.A.; PROKHOROV, A.N.; SHUMAKOV, I.A.; MIROSHINA, Yu.N.; SHAGALOV, Ye.S., red.;

[Album of sketches of stock equipment for the erection of structural elements] Al'bom chertezhei inventarnykh prispoblenii dlia vozvedeniia stroitel'nykh konstruktsii. Moskva. Pt.1.[Cradles, stagings, ladders, guard rails. Approved by a resolution of the technical administration No.163 of Dec. 30, 1959] Liul'ki, ploshchadki, lestnitsy, ograzhdeniia. Uverzhden resheniem tekhnicheskogo upravleniia No.163 ot 30 dekabria 1959 g. 141 p.

(MIRA 15:10)

1. Vsesoyuznyy institut po proyektirovaniyu organizatsii energeticheskogo stroitel'stva "ORGENERGOSTROI." Moskovskiy filial.

(Building)

BERENSHTEYN, S.A.; VAYSLEYB, V.P.; VARENIK, I.F.; DOBRYNCHENKO, M.V.;
YEGOROV, B.P.; KLISENKO, Yu.F.; MOGILEVSKIY, I.I. [deceased];
PEREYASLAVTSEV, N.A.; PILIPENKO, V.I.; SAPOZHNIKOV, F.V., inzh.;
SHEPELEV, V.M.; SIMULEVICH, M.L.; YARMOLINSKIY, I.M.; SHAGALOV,
Ye.S., red.; KORIKOVSKIY, I.K., red.; LARIONOV, G.Ye., tekhn. red.

[Construction of the V.I. Lenin State Regional Electric Power
Plant in Simferopol] Opyt stroitel'stva Simferopol'skoi GRES
im. V.I. Lenina [By] S.A. Berenshtein i dr. Moskva, Gosenergoizdat,
1962. 151 p. (MIRA 15:6)

(Simferopol--Electric power plants)

BAKHMETOVA, T.Ye., inzh.; DOVGHER, F.F., inzh.[deceased]; MIROSHINA, Yu.N., inzh.; PROKNGROV, A.N., inzh.; SMIRNOV, P.A., inzh.; SHUMAKOV, I.A , inzh.; SHAGALOV, Ye.S., red.

[Album of drawings of stock equipment for the erection of structural elements] Al'bom chertezhei inventarnykh prispособlenii dlia vozvedeniia stroitel'nykh konstruktsii. Moskva. Pt.2. [Scaffolding, trestles, trench shoring] Lesa, podmosti, krepleniia tran-shei. Utverzhden resheniem tekhnicheskogo upravleniia. No.61 ot 19 marta 1960 g. 1962. 113 p. (MIRA 16:2)

1. Vsesoyuznyy institut po proyektirovaniyu organizatsii energeticheskogo stroitel'stva "Orgenergostroy." Moskovskiy filial. (Scaffolding) (Shoring and underpinning)

TEITLIN, L.A. [Tseytlin, L.A.]; ELTISEVA, A.A. [Yeltysheva, A.A.]; GRAFAS,
N.I.; TIGANOV, A.S. [TSyganov, A.C.]; SAFARENKO, D.I.;
SAGALOVA, B.I. [Shagalova, B.I.]

Crucibles of the electric induction furnaces made of a given
filling material for the melting of aluminum alloys. Analele
metalurgie 16 no.4:75-80 O-D '62.

85553

S/131/60/000/011/001/002
B021/B058

15.3000 *also 2311*

AUTHORS: Gaylit, A. A., Grafas, N. I., Tsyganov, A. S., Shagalova, B. Yu., Nekrasov, K. D., Sassa, V. S.

TITLE: Experimental Use of Heat-resistant Concrete ✓

PERIODICAL: Ogneupory, 1960, No. 11, pp. 520-523

TEXT: The applicability of heat-resistant concrete for lining crucible induction furnaces was studied at the Moskovskiy zavod alyuminiyevykh splavov (Moscow Plant for Aluminum Alloys). The laboratory for heat-resistant concretes developed the concrete composition on the basis of investigations. The following materials were required for 1 m³ of concrete: 800 kg coarse-grained and 500 kg fine-grained fire-clay filler, 550 kg fine-ground magnesite, 18 to 21 kg commercial sodium fluosilicate and 300 to 350 kg liquid glass with a density of from 1.36 to 1.38 g/cm³. The molten glass corresponded to ГОСТ 962-41 (GOST 962-41), its modulus amounted to 2.4 to 3.0. The weight by volume of the heat-resistant concrete in dry state amounted to 2.2 g/cm³, the fire shrinkage at temperatures up to 1400°C to 0.2%. The mean linear thermal-expansion coefficient amounted to

Card 1/3

85553

Experimental Use of Heat-resistant Concrete

S/131/60/000/011/001/002
B021/B058

6.7.10⁻⁶ in the range of from 20 to 1000°C. The superior properties of heat-resistant concrete make it possible to build and dry a crucible induction furnace within seven days. The crucible with a wall thickness of 60 mm was made in a split mold by means of a vibration device (Fig. 1). The inductor lining was rammed at the Podol'skiy zavod tsvetnykh metallov (Podol'sk Plant for Nonferrous Metals). This work was conducted by a group of engineers under the supervision of the Nauchno-issledovatel'skiy institut betona i zhelezobetona (Scientific Research Institute of Concrete and Reinforced Concrete). The graphic representation of the drying and annealing of the crucible is shown in Fig. 2 and a dried crucible made of heat-resistant concrete in Fig. 3. The mechanical properties of the alloy АЛ10У (AL10ch) molten in this furnace are higher than when molten in a radiation furnace. The crucibles made from heat-resistant concrete may be used for melting various nonferrous metals with a melting temperature of up to 1200°C. The results are: total drying and annealing time 140 hrs, aluminum alloys were molten for 2.5 months with up to 15 heats per day. The crucible withstood 700 heats. About 116 tons of metal were molten. After 700 heats, cracks up to 0.7 mm wide were found. Experiments for the manufacture and test of larger crucibles are intended. The

Card 2/3

Experimental Use of Heat-resistant Concrete

S/131/60/000/011/001/002
B021/B058

applicability of heat-resistant concrete of various composition for crucible induction furnaces and other metallurgical aggregates is to be studied. There are 3 figures.

ASSOCIATION: Moskovskiy zavod alyuminiyevykh splavov (Moscow Plant for Aluminum Alloys) Gaylit, A. A., Grafas, N. I., Tsyganov, A. S., Shagalova, B. Yu.; Nauchno-issledovatel'skiy institut betona i zhelezobetona Akademii stroitel'stva i arkhitektury SSSR (Scientific Research Institute of Concrete and Reinforced Concrete of the Academy of Construction Engineering and Architecture USSR) Nekrasov, K. D., Sassa, V. S. X

Card 3/3

TSEYTLIN, L.A.; YELTYSHEVA, A.A.; GRAFAS, N.I.; TSYGANOV, A.S.; SHAFARENKO,
D.I.; SHAGALOVA, B.Yu.

Induction furnace crucibles made of rammed materials, for the
smelting of aluminum alloys. TSvet. met. 35 no.5:71-75 My
'62. (MIRA 16:5)

(Aluminum alloys—Electrometallurgy) (Crucibles)

IVANOV, S.N.; SHAGALOVA, E.D.

Use of p^{32} for studying the phosphorus uptake by early cabbage
using various methods of fertilizer placement. Dokl. AN BSSR
8 no. 1:57-59 Ja '64. (MIRA 17:5)

1. Nauchno-issledovatel'skiy institut pochvovedeniya Ministerstva
sel'skogo khozyaystva BSSR.

SHAGALOVA, L.A.

Propagation of ultrasonic waves in polymer solutions.
 I. G. Mikhailov and L. A. Shagalova. *Doklady Akad. Nauk S.S.S.R.* 89, 826-828 (1953). English translation issued as *U.S. Atomic Energy Comm. NSF-tr-117, 1-4* (1953).
 The absorption and velocity of ultrasonic waves were detd. for a 13.4% aq. polyvinyl alc. soln., a 6.4% polyisobutylene soln. in benzene, polystyrene solns. in benzene, and Oppanol solns. in transformer oil. The absorption was measured both by a pulse method using a modified Sokolov defectoscope with carrier frequencies of 1.25, 2.50, and 3.75 Mc./sec., and by a prism method previously developed by M. and Solov'yev (*C.A.* 45, 7839i) utilizing brass shells in the shape of prisms. The wave velocity was detd. with an ultrasonic interferometer. Values for the ratio of the absorption coeff. to the square of the frequency used, α/ν^2 , were detd. From viscosities measured in an Ostwald viscometer, α/ν^2 was calcd. from Stoke's formula as 4400×10^{-12} and $12,000 \times 10^{-12}$ for the polyvinyl alc. and polyisobutylene solns., resp. The observed α was too small to be detected, and thus $\alpha/\nu^2 < 200 \times 10^{-12}$. The structural formation in the polystyrene solns. was considered to be weak, since no dependence of the viscosity on the velocity gradient was found except at the highest concn. studied, 14.2%. The absorption coeff. increased only slightly with concn.; this indicated that the mechanism of sound propagation was the same in solns. having weak structural formation and in completely structured solns. such as gelatin (M. and Tarutina, *C.A.* 45, 416d). As for the polystyrene solns., the Oppanol in transformer oil solns. showed a much smaller dependence of α on concn. than predicted from Stoke's formula. The data obtained indicated that the use of a completely stationary network model was inapplicable to ultrasonic propagation in polymeric solns. Values calcd. from the Gotlib-Vol'kenshtein equation (cf. preceding abstr.) agreed with the exptl. data for the polystyrene solns. Philip Goodman

SHAGALOVA, L. I.

USSR/Chemistry - Cellulose Acetate

Jun 52

"Stabilization of Cellulose Triacetate Film Against Deterioration Due to Oxidation at High Temperatures," A. A. Freyman, V. A. Bartashev, L. I. Shagalova, et al, Leningrad Inst of Motion Picture Engineers, Lab of Motion Picture Film Base Technol

"Zhur Frik Khim" Vol XXV, No 6, pp 626-633

The stability of triacetate films, used in particular as elec insulation material, toward air, high temps, and other factors, can be increased by addn of special substances. Analyzed the gaseous phase in an app contg triacetate film both with and without stabilizer. The film was in an oxygen medium at temps of 80 to 140°C. Film samples dept at the same temps in nitrogen were used for comparison. Pyrogallol, α -naphthylamine, phenyl- β -naphthylamine and phenyl- β -naphthylamine were tested for action as stabilizers. The latter 2 were found to be the most effective.

218T34

SHAGALOVA, L. I.

Chemical Abst.
Vol. 48 No. 9
May 10, 1954
Cellulose and Paper

⑥ *matte*
Stabilization of cellulose triacetate films against thermo-oxidative destruction. A. A. Freeman, V. A. Barlashev, V. I. Shagalova, V. V. Ganneman, G. P. Marova, and L. I. Shagalova. *App. Chem. U.S.S.R.* 25, 106-11 (1952) (Engl. translation).—See C.A. 47, 2970g. H. L. H.

9-17-54

SHAGALOVA, L. I.

USSR/Chemistry - Photofilm Stabilizers

Aug 52

"The Change in the Amount of Stabilizers in Triacetate Films During Destruction by Oxidation at Elevated Temperatures," A. A. Freyman, V. A. Bartashov, L. I. Shagalova, N. L. Perfileva, V. D. Kurchenko, Lab of Techno for Moving Picture Film Base, Lenin-grad Inst of Moving Picture Film Engineers

"Zhur Prik Khim" Vol 25, No 8, 884-889

States that stabilizers present in films are subject to chem change to a greater deg than stabilizers in their free form, under similar conditions. The nature of the change in the quantity of phenyl- α -naphthylamine and phenyl- β -naphthylamine is identical in films. During the process of oxidation, the amt of stabilizer changed, whereas there was no thermal decompn of phenyl- β -naphthylamine when heated at 140 $^{\circ}$ C. Intermediate products of the oxidation of aromatic amines were also shown to be stabilizers of triacetate films. The action of oxygen on plasticized, stabilized films, at a temp of 140 $^{\circ}$ C, was studied. The simultaneous presence of a stabilizer (secondary amine) and dibutylphthalate assured a greater resistance of both to the effect of oxygen at high temps.

PA 228T13

1. SHAGALOVA, L. I.; FREYMAN, A. A.
 2. USSR (600)
 4. Cellulose Triacetate
 7. Study of stabilization of cellulose triacetate films by secondary aromatic amines at high temperatures or by ultraviolet radiation in air. Zhur. prikl. khi 25 no. 10, 1952.
9. Monthly List of Russian Accessions, Library of Congress, January 1953. Unclassified.

GAYLIT, A.A.; GRAFAS, N.I.; TSYGANOV, A.S.; SHAGALOVA, B.Yu. NEKRASOV, K.D.;
SASSA, V.S.

Practices of using heat resistant concrete. Ogneupory 25 no.11:520-
523 '60. (MIRA 13:12)

1. Moskovskiy zavod alyuminiyevykh splavov (for Gaylit, Grafas,
TSyganov, Shagalova). 2. Nauchno-issledovatel'skiy institut betona
i zhelezobetona Akademii stroitel'stva i arkhitektury SSSR (for
Nekrasov, Sassa).

(Concrete—Curing)

1ST AND 2ND CODES																										PROCESSING AND PROPERTIES INDEX																									
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100																																																			
BC																																																			
<p>Production of monohydroxy and nonyl alcohol. R. KUSAKABE (Mitsui. Sait. Date. 1955, 11, 453-455).—An improved prep. from undecanoic acid is described.</p>																																																			
ASB-5LA METALLURGICAL LITERATURE CLASSIFICATION																																																			
<p>EXON: 110-83190</p> <p>EXON: 110-83190</p>																																																			
<p>EXON: 110-83190</p> <p>EXON: 110-83190</p>																																																			

10

cd

PROCESSES AND PROPERTIES INDEX

Production of nonylaldehyde and nonyl alcohol. R. Shagalova. *Makobolna Zhivore Delo* 11, 452 3(1935).

The Hesse method of production of nonylaldehyde (I) and nonyl alc. (II) by fusing undecylenic acid with KOH to give pelargonic acid (III); reducing the Et pelargonate with Na in abs. alc. to II and oxidizing the latter to I. was modified by reducing III in the presence of a MnO catalyst to I of high purity with 60-5% yield. The method of reducing I to II is being investigated. R.

ASD-SLA METALLURGICAL LITERATURE CLASSIFICATION

REGION 80-1000

REGION 80-1000

PROCEDURES AND PROPERTIES INDEX																									
1ST AND 2ND ORDERS													3RD AND 4TH ORDERS												
<p><i>ca</i></p> <p>Decylaldehyde from the oil of blooming coriander L. Ya. Bryusova, R. Yu. Shagalova and N. Novikova <i>Sovetskii Dushivnykh Veshchev, Sbornik State 1939, 217-22.</i> <i>Khm. Referat. Zhur. 1940, No. 1, 117-18.</i> Coriander oil obtained from coriander seeds consists only partly of decylaldehyde. The oil of the green parts of the same plant contains up to 95% of aldehydes, 10% of which is decylaldehyde. Coriander oil used for producing decyl- aldehyde contained 51% of aldehydes and had acid no. 2.3, ether no. 25, n_D^{20} 1.4500. Fractionation of the oil pro- duced a fraction containing a high percentage of the aldehyde. This fraction was hydrogenated with a 10-12% excess of H in alc. at 40-55° in the presence of a Ni catalyst. The decylaldehyde obtained after a 2-fold fractionation b. 75-7°, d_4^{20} 0.839, n_D^{20} 1.4340, mol. refraction 18.16 (when calcd. to $C_{11}H_{22}$ it is 18.30); oxime, m. 60°; semicarba- zone m. 101.5-2.5°. These const. differ slightly from those given in the chem. literature. The yield of decyl- aldehyde is approx. 30% of the aldehydes contained in the oil. W. R. Henn</p>																									
<p>ASB. S.L.A. METALLURGICAL LITERATURE CLASSIFICATION</p> <p>EXON. CIV. 21311</p> <p>EXON. 21311</p> <p>EXON. 21311</p>																									

1ST AND 2ND ORDERS																										3RD AND 4TH ORDERS																																																																																																																												
PROCESS AND PROPERTIES INDEX																																																																																																																																																						
<p>Production of enanthaldehyde and hendecenoic acid by pyrogenetic decomposition of methyl ricinoleate. S. S. Nametkin and R. Yu. Shagubova: <i>Sintezy Dushivlykh Veshchestv, Sbornik Statei</i> 1939, 261-71; <i>Khim. Referat. Zhur.</i> 1940, No. 4, 118.—The initial raw material used for the expts. was tech. Me ricinoleate obtained from castor oil and MeOH, at first according to the method of Haller (C. A. 1, 1387) in the presence of 1% dry HCl, and later according to the method modified by N. and S. with oleum (not more than 5% of the wt. of castor oil) instead of HCl. The reaction was carried out at 67-8°. The Me ricinoleate obtained was decmpled. pyrogenetically at 350°, in a 360-mm. vacuum and with a velocity of the ester of 2 kg./hr. Pyrolysis was carried out in a Cu tube (1.5 m. long, 12 mm. diam.) in an elec. oven. The product contg. 25-8% of aldehyde was distd. with water vapor, producing a complete sepn. of enanthole. The yield of enanthole contg. 90-5% of the aldehyde was 17-18% (of the castor oil used for the reaction). The enanthole had d_4^{20} 0.821 and n_D^{20} 1.418. The residue remaining after the distn. of enanthole is a mixt. of esters of hendecenoic acid. It was sapond. and fractionated, producing 95-7% hendecenoic acid which did not require a further purification; the yield was 25-7% of the wt. of castor oil used for the reaction.</p> <p style="text-align: right;">W. R. Henn</p>																																																																																																																																																						
ASB-5LA METALLURGICAL LITERATURE CLASSIFICATION																																																																																																																																																						
<table border="1"> <tr> <td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18</td><td>19</td><td>20</td><td>21</td><td>22</td><td>23</td><td>24</td><td>25</td><td>26</td><td>27</td><td>28</td><td>29</td><td>30</td><td>31</td><td>32</td><td>33</td><td>34</td><td>35</td><td>36</td><td>37</td><td>38</td><td>39</td><td>40</td><td>41</td><td>42</td><td>43</td><td>44</td><td>45</td><td>46</td><td>47</td><td>48</td><td>49</td><td>50</td><td>51</td><td>52</td><td>53</td><td>54</td><td>55</td><td>56</td><td>57</td><td>58</td><td>59</td><td>60</td><td>61</td><td>62</td><td>63</td><td>64</td><td>65</td><td>66</td><td>67</td><td>68</td><td>69</td><td>70</td><td>71</td><td>72</td><td>73</td><td>74</td><td>75</td><td>76</td><td>77</td><td>78</td><td>79</td><td>80</td><td>81</td><td>82</td><td>83</td><td>84</td><td>85</td><td>86</td><td>87</td><td>88</td><td>89</td><td>90</td><td>91</td><td>92</td><td>93</td><td>94</td><td>95</td><td>96</td><td>97</td><td>98</td><td>99</td><td>100</td> </tr> </table>																																																			1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100																																																			

PROCESSES AND PROPERTIES INDEX																									
1ST AND 2ND CROSSL													100 AND 4TH CROSSL												
<p>ca</p> <p>10</p> <p>Production of jasmine aldehyde. S. S. Nametkin and R. V. Shagakova. <i>Sintezy Dushistykh Veshchestv, Nbr 10, State 1939, 271-4; Khim. Referat. Zhur. 1940.</i></p> <p>No. 4, 118.—The synthesis of jasmine aldehyde (α-amylcinnamaldehyde) was carried out by condensation of enanthole with BzH. Max. yields of jasmine aldehyde were obtained from condensation in aq. alc. with a 1:5 ratio of enanthole to BzH and approx. 1% excess of base. A product suitable for <i>perfumery purposes</i> was obtained by fractionating the tech. product at 5 mm. at 140-1°. The by-products included $BzOH$, benzyl alc. and a complex ester whose nature has not been detd. W. R. H.</p>																									
ASR-SLA METALLURGICAL LITERATURE CLASSIFICATION																									
12000 17000 18000 19000 20000 21000 22000 23000 24000 25000 26000 27000 28000 29000 30000 31000 32000 33000 34000 35000 36000 37000 38000 39000 40000 41000 42000 43000 44000 45000 46000 47000 48000 49000 50000 51000 52000 53000 54000 55000 56000 57000 58000 59000 60000 61000 62000 63000 64000 65000 66000 67000 68000 69000 70000 71000 72000 73000 74000 75000 76000 77000 78000 79000 80000 81000 82000 83000 84000 85000 86000 87000 88000 89000 90000 91000 92000 93000 94000 95000 96000 97000 98000 99000 100000 101000 102000 103000 104000 105000 106000 107000 108000 109000 110000 111000 112000 113000 114000 115000 116000 117000 118000 119000 120000 121000 122000 123000 124000 125000 126000 127000 128000 129000 130000 131000 132000 133000 134000 135000 136000 137000 138000 139000 140000 141000 142000 143000 144000 145000 146000 147000 148000 149000 150000 151000 152000 153000 154000 155000 156000 157000 158000 159000 160000 161000 162000 163000 164000 165000 166000 167000 168000 169000 170000 171000 172000 173000 174000 175000 176000 177000 178000 179000 180000 181000 182000 183000 184000 185000 186000 187000 188000 189000 190000 191000 192000 193000 194000 195000 196000 197000 198000 199000 200000 201000 202000 203000 204000 205000 206000 207000 208000 209000 210000 211000 212000 213000 214000 215000 216000 217000 218000 219000 220000 221000 222000 223000 224000 225000 226000 227000 228000 229000 230000 231000 232000 233000 234000 235000 236000 237000 238000 239000 240000 241000 242000 243000 244000 245000 246000 247000 248000 249000 250000 251000 252000 253000 254000 255000 256000 257000 258000 259000 260000 261000 262000 263000 264000 265000 266000 267000 268000 269000 270000 271000 272000 273000 274000 275000 276000 277000 278000 279000 280000 281000 282000 283000 284000 285000 286000 287000 288000 289000 290000 291000 292000 293000 294000 295000 296000 297000 298000 299000 300000 301000 302000 303000 304000 305000 306000 307000 308000 309000 310000 311000 312000 313000 314000 315000 316000 317000 318000 319000 320000 321000 322000 323000 324000 325000 326000 327000 328000 329000 330000 331000 332000 333000 334000 335000 336000 337000 338000 339000 340000 341000 342000 343000 344000 345000 346000 347000 348000 349000 350000 351000 352000 353000 354000 355000 356000 357000 358000 359000 360000 361000 362000 363000 364000 365000 366000 367000 368000 369000 370000 371000 372000 373000 374000 375000 376000 377000 378000 379000 380000 381000 382000 383000 384000 385000 386000 387000 388000 389000 390000 391000 392000 393000 394000 395000 396000 397000 398000 399000 400000 401000 402000 403000 404000 405000 406000 407000 408000 409000 410000 411000 412000 413000 414000 415000 416000 417000 418000 419000 420000 421000 422000 423000 424000 425000 426000 427000 428000 429000 430000 431000 432000 433000 434000 435000 436000 437000 438000 439000 440000 441000 442000 443000 444000 445000 446000 447000 448000 449000 450000 451000 452000 453000 454000 455000 456000 457000 458000 459000 460000 461000 462000 463000 464000 465000 466000 467000 468000 469000 470000 471000 472000 473000 474000 475000 476000 477000 478000 479000 480000 481000 482000 483000 484000 485000 486000 487000 488000 489000 490000 491000 492000 493000 494000 495000 496000 497000 498000 499000 500000 501000 502000 503000 504000 505000 506000 507000 508000 509000 510000 511000 512000 513000 514000 515000 516000 517000 518000 519000 520000 521000 522000 523000 524000 525000 526000 527000 528000 529000 530000 531000 532000 533000 534000 535000 536000 537000 538000 539000 540000 541000 542000 543000 544000 545000 546000 547000 548000 549000 550000 551000 552000 553000 554000 555000 556000 557000 558000 559000 560000 561000 562000 563000 564000 565000 566000 567000 568000 569000 570000 571000 572000 573000 574000 575000 576000 577000 578000 579000 580000 581000 582000 583000 584000 585000 586000 587000 588000 589000 590000 591000 592000 593000 594000 595000 596000 597000 598000 599000 600000 601000 602000 603000 604000 605000 606000 607000 608000 609000 610000 611000 612000 613000 614000 615000 616000 617000 618000 619000 620000 621000 622000 623000 624000 625000 626000 627000 628000 629000 630000 631000 632000 633000 634000 635000 636000 637000 638000 639000 640000 641000 642000 643000 644000 645000 646000 647000 648000 649000 650000 651000 652000 653000 654000 655000 656000 657000 658000 659000 660000 661000 662000 663000 664000 665000 666000 667000 668000 669000 670000 671000 672000 673000 674000 675000 676000 677000 678000 679000 680000 681000 682000 683000 684000 685000 686000 687000 688000 689000 690000 691000 692000 693000 694000 695000 696000 697000 698000 699000 700000 701000 702000 703000 704000 705000 706000 707000 708000 709000 710000 711000 712000 713000 714000 715000 716000 717000 718000 719000 720000 721000 722000 723000 724000 725000 726000 727000 728000 729000 730000 731000 732000 733000 734000 735000 736000 737000 738000 739000 740000 741000 742000 743000 744000 745000 746000 747000 748000 749000 750000 751000 752000 753000 754000 755000 756000 757000 758000 759000 760000 761000 762000 763000 764000 765000 766000 767000 768000 769000 770000 771000 772000 773000 774000 775000 776000 777000 778000 779000 780000 781000 782000 783000 784000 785000 786000 787000 788000 789000 790000 791000 792000 793000 794000 795000 796000 797000 798000 799000 800000 801000 802000 803000 804000 805000 806000 807000 808000 809000 810000 811000 812000 813000 814000 815000 816000 817000 818000 819000 820000 821000 822000 823000 824000 825000 826000 827000 828000 829000 830000 831000 832000 833000 834000 835000 836000 837000 838000 839000 840000 841000 842000 843000 844000 845000 846000 847000 848000 849000 850000 851000 852000 853000 854000 855000 856000 857000 858000 859000 860000 861000 862000 863000 864000 865000 866000 867000 868000 869000 870000 871000 872000 873000 874000 875000 876000 877000 878000 879000 880000 881000 882000 883000 884000 885000 886000 887000 888000 889000 890000 891000 892000 893000 894000 895000 896000 897000 898000 899000 900000 901000 902000 903000 904000 905000 906000 907000 908000 909000 910000 911000 912000 913000 914000 915000 916000 917000 918000 919000 920000 921000 922000 923000 924000 925000 926000 927000 928000 929000 930000 931000 932000 933000 934000 935000 936000 937000 938000 939000 940000 941000 942000 943000 944000 945000 946000 947000 948000 949000 950000 951000 952000 953000 954000 955000 956000 957000 958000 959000 960000 961000 962000 963000 964000 965000 966000 967000 968000 969000 970000 971000 972000 973000 974000 975000 976000 977000 978000 979000 980000 981000 982000 983000 984000 985000 986000 987000 988000 989000 990000 991000 992000 993000 994000 995000 996000 997000 998000 999000 1000000 1001000 1002000 1003000 1004000 1005000 1006000 1007000 1008000 1009000 1010000 1011000 1012000 1013000 1014000 1015000 1016000 1017000 1018000 1019000 1020000 1021000 1022000 1023000 1024000 1025000 1026000 1027000 1028000 1029000 1030000 1031000 1032000 1033000 1034000 1035000 1036000 1037000 1038000 1039000 1040000 1041000 1042000 1043000 1044000 1045000 1046000 1047000 1048000 1049000 1050000 1051000 1052000 1053000 1054000 1055000 1056000 1057000 1058000 1059000 1060000 1061000 1062000 1063000 1064000 1065000 1066000 1067000 1068000 1069000 1070000 1071000 1072000 1073000 1074000 1075000 1076000 1077000 1078000 1079000 1080000 1081000 1082000 1083000 1084000 1085000 1086000 1087000 1088000 1089000 1090000 1091000 1092000 1093000 1094000 1095000 1096000 1097000 1098000 1099000 1100000 1101000 1102000 1103000 1104000 1105000 1106000 1107000 1108000 1109000 1110000 1111000 1112000 1113000 1114000 1115000 1116000 1117000 1118000 1119000 1120000 1121000 1122000 1123000 1124000 1125000 1126000 1127000 1128000 1129000 1130000 1131000 1132000 1133000 1134000 1135000 1136000 1137000 1138000 1139000 1140000 1141000 1142000 1143000 1144000 1145000 1146000 1147000 1148000 1149000 1150000 1151000 1152000 1153000 1154000 1155000 1156000 1157000 1158000 1159000 1160000 1161000 1162000 1163000 1164000 1165000 1166000 1167000 1168000 1169000 1170000 1171000 1172000 1173000 1174000 1175000 1176000 1177000 1178000 1179000 1180000 1181000 1182000 1183000 1184000 1185000 1186000 1187000 1188000 1189000 1190000 1191000 1192000 1193000 1194000 1195000 1196000 1197000 1198000 1199000 1200000 1201000 1202000 1203000 1204000 1205000 1206000 1207000 1208000 1209000 1210000 1211000 1212000 1213000 1214000 1215000 1216000 1217000 1218000 1219000 1220000 1221000 1222000 1223000 1224000 1225000 1226000 1227000 1228000 1229000 1230000 1231000 1232000 1233000 1234000 1235000 1236000 1237000 1238000 1239000 1240000 1241000 1242000 1243000 1244000 1245000 1246000 1247000 1248000 1249000 1250000 1251000 1252000 1253000 1254000 1255000 1256000 1257000 1258000 1259000 1260000 1261000 1262000 1263000 1264000 1265000 1266000 1267000 1268000 1269000 1270000 1271000 1272000 1273000 1274000 1275000 1276000 1277000 1278000 1279000 1280000 1281000 1282000 1283000 1284000 1285000 1286000 1287000 1288000 1289000 1290000 1291000 1292000 1293000 1294000 1295000 1296000 1297000 1298000 1299000 1300000 1301000 1302000 1303000 1304000 1305000 1306000 1307000 1308000 1309000 1310000 1311000 1312000 1313000 1314000 1315000 1316000 1317000 1318000 1319000 1320000 1321000 1322000 1323000 1324000 1325000 1326000 1327000 1328000 1329000 1330000 1331000 1332000 1333000 1334000 1335000 1336000 1337000 1338000 1339000 1340000 1341000 1342000 1343000 1344000 1345000 1346000 1347000 1348000 1349000 1350000 1351000 1352000 1353000 1354000 1355000 1356000 1357000 1358000 1359000 1360000 1361000 1362000 1363000 1364000 1365000 1366000 1367000 1368000 1369000 1370000 1371000 1372000 1373000 1374000 1375000 1376000 1377000 1378000 1379000 1380000 1381000 1382000 1383000 1384000 1385000 1386000 1387000 1388000 1389000 1390000 1391000 1392000 1393000 1394000 1395000 1396000 1397000 1398000 1399000 1400000 1401000 1402000 1403000 1404000 1405000 1406000 1407000 1408000 1409000 1410000 1411000 1412000 1413000 1414000 1415000 1416000 1417000 1418000 1419000 1420000 1421000 1422000 1423000 1424000 1425000 1426000 1427000 1428000 1429000 1430000 1431000 1432000 1433000 1434000 1435000 1436000 1437000 1438000 1439000 1440000 1441000 1442000 1443000 1444000 1445000 1446000 1447000 1448000 1449000 1450000 1451000 1452000 1453000 1454000 1455000 1456000 1457000 1458000 1459000 1460000 1461000 1462000 1463000 1464000 1465000 1466000 1467000 1468000 1469000 1470000 1471000 1472000 1473000 1474000 1475000 1476000 1477000 1478000 1479000 1480000 1481000 1482000 1483000 1484000 1485000 1486000 1487000 1488000 1489000 1490000 1491000 1492000 1493000 1494000 1495000 1496000 1497000 1498000 1499000 1500000 1501000 1502000 1503000 1504000 1505000 1506000 1507000 1508000 1509000 1510000 1511000 1512000 1513000 1514000 1515000 1516000 1517000 1518000 1519000 1520000 1521000 1522000 1523000 1524000 1525000 1526000 1527000 1528000 1529000 1530000 1531000 1532000 1533000 1534000 1535000 1536000 1537000 1538000 1539000 1540000 1541000 1542000 1543000 1544000 1545000 1546000 1547000 1548000 1549000 1550000 1551000 1552000 1553000 1554000 1555000 1556000 1557000 1558000 1559000 1560000 1561000 1562000 1563000 1564000 1565000 1566000 1567000 1568000 1569000 1570000 1571000 1572000 1573000 1574000 1575000 1576000 1577000 1578000 1579000 1580000 1581000 1582000 1583000 1584000 1585000 1586000 1587000 1588000 1589000 1590000 1591000 1592000 1593000 1594000 1595000 1596000 1597000 1598000 1599000 1600000 1601000 1602000 1603000 1604000 1605000 1606000 1607000 1608000 1609000 1610000 1611000 1612000 1613000 1614000 1615000 1616000 1617000 1618000 1619000 1620000 1621000 1622000 1623000 1624000 1625000 1626000 1627000 16280																									

<p>10</p> <p>Production of nonaldehyde and nonyl alcohol. S. S. Nametkin and R. Yu. Shagalova, <i>Sintezy Dushivnykh Veshchestv, Sbornik State 1938</i>, 274-81; <i>Khim. Referat. Zhur.</i> 1940, No. 4, 118-119. — Nonole acid was used as the initial substance for producing nonaldehyde and nonyl alc. The Kraft-Hesse method based on fusing hendecenoic acid with base was used for the expts. The reaction is completed when no more foam is formed. Cool the mass, add cold water until it dissolves completely and sep. the tech. nonyl alc. by adding tech. HCl. Fractionation of the nonole acid gives a fraction contg. 97-8% nonole acid (65-70% of the wt. of hendecenoic acid instead of the 28% obtained by Hesse). Nonylaldehyde was obtained by reduction of the acid in a current of CO₂ according to the method developed by Nametkin and Khol'mer for obtaining lauraldehyde (<i>C. A.</i> 36, 3629). The yield of nonylaldehyde, d₄ 0.880, n_D 1.4240, suitable for <i>perfumery purposes</i> was 50-5 wt. % or 56-62% of the theoretical. Nonyl alc. was obtained by 2 methods: according to Bouveault (<i>C. A.</i> 16, 1911) and by hydrogenation. Et nonole obtained according to Bouveault was reduced with metallic Na. The yield of alc., d₄ 0.827, n_D 1.435, was 75-80% of the theoretical (instead of 43% given in the literature). In the hydrogenation method H was passed through the bisulfite compd. of the aldehyde in the presence of a pyrophoric Ni catalyst in alc. The reaction was carried out at 55-60° for 4-5 hrs. The yield of nonyl alc. suitable for <i>perfumery purposes</i> was 70-5%.</p>																									
<p>ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION</p>																									

SHAGALOVA, R. Yu. Cand. Chem. Sci.

Dissertation: "Preparation of Enauthol and Undecylenic Acid by Pyrogenic Decomposition of the Methyl Ether of Ricinoleic Acid and Their Utilization in the Synthesis of Scented Substances." All-Union Sci Res Inst of Synthetic and Natural Essential Oils, 26 Dec 47.

SO: Vechernyaya Moskva, Dec, 1947 (Project #17836)

SHAGALOVA, R.Yu.; DAYEV, N.A.; GOL'PERIN, N.I.; KUZNETSOVA, M.P.

Some improvements in the chloral method for the production of
vanillin and vanillal. Trudy VNIISNDV no.4:34-38 '58.
(MIRA 12:5)

(Vanillin) (Bourbonal) (Chloral)

SHAGALOVA, S.A., kand. tekhn. nauk; REZNIK, V.A., inzh.

Effect of initial pressures on the nature of the development of
dust explosions in natural fuels. Teploenergetika 12 no.7:63-65
Jl '65. (MIRA 18:7)

1. Tsentral'nyy kotloturbinnyy institut.

SHAGALOVA, S. L.

Dissertation: "Low Temperature Oxidation and Spontaneous Combustion of Natural Fuels."
Cand Tech Sci, Central Sci Res Boiler-Turbine Institute I. I. Polzunov (TsKTI), Leningrad,
1953. Referativnyy Zhurnal--Khimiya, Moscow, No 14, Jul 54.

SC: SUM No. 356, 25 Jan 1955

SHAGALOVA, S.L., kandidat tekhnicheskikh nauk.

Analysis of conditions leading to spontaneous combustion of natural
fuels. [Trudy] TSMTI 26:189-230 '54. (MIRA 8:2)
(Combustion, Spontaneous) (Fuel)

SHAGALOVA, S.L.

AID P - 2323

Subject : USSR/Engineering

Card 1/1, Pub. 110-a - 4/17

Author : Shagalova, S. L., Kand. of Tech. Sci.

Title : Research on explosiveness of **pulverized fuel** dust

Periodical : Teploenergetika, 5, 22-25, My 1955

Abstract : The author reports a study made on the explosiveness of pulverized coal and peat dust. A detailed description and diagram of the experimental installation are given. The data on the explosive properties of various coals and peat are summed up in tables and illustrated by curves. Eight Russian, 1933-1948 and 1 English reference, 1948.

Institution : Central Turbine-Boiler Institute

Submitted : No date

BHAGALOVA, S. L., POMERANTSEV, V. V. and KATSNEL'SON, B. D.
(Masters of Science)

"Physical and Chemical Laws of the Process of Combustion of Natural Fuel,"
paper presented at the 5th World Power Conference, Vienna, 1956

In Branch # 5

POMERANTSEV, V. V., Cand. Tech. Sci.; KATSNELSON, B. D., Cand. Tech. Sci.; SHAGALOVA, S. L.,
Cand. Tech. Sci.

"Physikalisch-chemische Gesetzmässigkeiten der Verbrennprozesse von natürlichen Brennstoffen," List of General Reports and Papers presented at the Fifth World Power Conference, Vienna, 10 January 1956, pg. 28.

E-2298

Shagalova, S.L.

56. FACTORS INFLUENCING DET EXPLOSIONS IN NATURAL FUELS.
 Shagalova, S.L. (Toploenergetika (Heat Power Engng, Moscow), Feb. 1957, 16-20).
 From experiments on the effect of particle size on coal dust explosions, graphs
 were obtained showing the decrease of intensity with particle size; and for
 peat, brown coal and bituminous coal, limiting particle sizes, above which an
 explosion would not take place, were determined. Moisture was shown to
 decrease the possibility of an explosion and limiting moisture contents for
 various solid fuels were obtained. Addition of a small amount of ash to peat
 was found to increase the ignition time and decrease the intensity of an
 explosion. Investigations on the effect of oxygen on the explosibility of
 dust, showed that with a lower oxygen concentration in the air, there was less
 likelihood of an explosion, but at the lower limits the starting of an explosion
 mostly depends on the amount of volatiles given off by the fuel. The effect
 of added carbon dioxide and of air temperature on the pressure produced by the
 explosion was also determined. (L).

SHAKALOVA, S. L., BERNSTEYN, R. S., Pomerantsev, V. V.,

"On the Mechanism of Resistance and Heat Loss in Clusters of Pipes," p 251, Aerodynamic and Heat Transfer Problems in Boiler and Furnace Processes; A Collection of Articles, Moscow, Gosenergoizdat, Moscow, 1958. 329 p.

Purpose: The book is intended for engineers and combustion specialists concerned with design and operation of heating equipment and it is also for scientific workers and students of vtuzes.

" Generalized Calculation Method for Aerodynamic Resistance of Filled Cross Sections, Ibid. p. 267

10.2000

68271

SOV/81-59-10-35116

Translation from: Referativnyy zhurnal. Khimiya, 1959, Nr 10, p 254 (USSR)

AUTHORS: Bernshteyn, R.S., Pomerantsev, V.V., Shagalova, S.L.

TITLE: The Problem of the Mechanism of Resistance and Heat Emission in Pipe Bundles

PERIODICAL: V sb.: Vopr. aerodinamiki i teploperedachi v kotel'no-topochn. protses-sakh. Moscow - Leningrad, Gosenergoizdat, 1958, pp 251-267

ABSTRACT: The distribution of the pressures and the coefficients of heat emission over the surface of porous pipes of 28 mm in diameter with air flowing around them in the case of artificial moistening of the pipe material have been investigated. The experiments were carried out in an aerodynamic pipe at stationary heat and hydrodynamic conditions with three pipe bundles arranged in the corridor type with the ratio of the steps $S_1/d = S_2/d = 1.13$; $S_1/d = 1.15$ and $S_2/d = 2.26$; $S_1/d = 2.26$ and $S_2/d = 1.13$ and also with two pipe bundles arranged in the chessboard order with the ratio of the steps $S_1/d = S_2/d = 1.2$; $S_1/d = 2.26$ and $S_2/d = 1.13$ within the range of the Re criterion 100 - 50,000. Based on the found fields of pressures and coefficients of heat emission on the surface of the pipes it has been shown that between the pipes of one and the same row a jet flow takes place; in the free section

Card 1/2

68271

SOV/81-59-10-35116

The Problem of the Mechanism of Resistance and Heat Emission in Pipe Bundles

between two adjacent rows of the bundle the character of the flow is similar to the character of a jet outflowing into an infinite filled space. It has also been established that a considerable effect on the distribution of the coefficients of heat emission on the circumference of the pipes is exercised by the change in the step of the bundle S_1/d . It has been noted that the first row shows the principal turbulizing action on the gas flow.

R. Artym

Card 2/2

904/81-59-8-27676

Translation from: Referativnyy zhurnal. Khimiya, 1959, Nr 8, p 306 (USSR)

AUTHORS: Bernshteyn, R.S., Pomerantsev, V.V., Shagalova, S.L.


TITLE: A Generalized Method for Calculating the Aerodynamic Resistance of Constrained Cross Sections

PERIODICAL: V sb.: Vopr. aerodinamiki i teploperedachi v kotel'no-topochn. protsessakh. Moscow-Leningrad, Gosenergoizdat, 1958, pp 267 - 289

ABSTRACT: Equations have been cited for calculating the hydraulic resistance for pipe bundles in the corridor and chessboard pattern arrangement of the pipes, as well as for the layer of lump- and ball-shaped particles, which are applicable to technical calculations.

V. Gertsovskiy

Card 1/1



SOV/96-58-11-6/21

AUTHOR: Pomerantsev, V.V., Doctor of Technical Science
Shakulova, S.L., Candidate of Technical Science
Aref'yev, A.M., Engineer

TITLE: An Approximate Method of Calculating the Combustion
of a Pulverised Fuel Flame (Priblizhennaya metodika
rascheta vygoraniya pyleugol'nogo fakela)

PERIODICAL: Teploenergetika 1958, Nr 11, pp 33-41 (USSR)

ABSTRACT: Previous work has established that the volatiles and
coke burn simultaneously in the early stages of
combustion of natural fuel. In fuel pulverised to
100 microns, the quantity of coke burned during the
time of simultaneous burning of volatiles and coke
is about 65 - 75%. As will be seen from Fig.1, the
remaining coke burns very slowly and as the
combustion time of the volatiles is so much less,
the total burning time of the fuel is mainly
governed by burning of the coke. For the purposes
of mathematical analysis the simplifying assumptions
are made that the pulverised fuel flame flows only
forward and is of uniform section; also that the
coke is ashless and the velocity and temperature

Card 1/7

SOV/96-58-11-6/21

An Approximate Method of Calculating the Combustion of a
Pulverised Fuel Flame

of the fuel particles are the same as the mean velocity and temperature of the gas. Tests show that these assumptions are valid for particles of up to 300 microns. The fundamentals of the calculation are explained in previously published articles and formulae are given for the combustion time of a particle of given size. On the basis of the equations that are derived, the condition of the flame at any given instant of time after a fuel particle enters the furnace is considered. Calculations are made of the quantity of fuel burning in a given time, the oxygen consumption, the oxygen concentration in the torch and the fuel particle size distribution. Finally a general solution is obtained from which are derived formulae for calculating the combustion of fuel dust in the diffusion and kinetic regions. For convenience of calculation, nomograms are constructed for equations 13, 21 and 22; these are given in Fig.4. These nomograms may be used to determine the combustion

Card 2/7

SOV/96-58-11-6/21

An Approximate Method of Calculating the Combustion of a
Pulverised Fuel Flame

time of the flame provided that the elementary and fractional composition of the coal particles, the calorific value of the fuel, the kinetic constants of the coke, the amount of mechanically-incomplete combustion, the excess-air factor and the mean temperature in the furnace chamber are given. The nomograms can also serve to determine the amount of mechanically-incomplete combustion after the torch has burned for a given time and to indicate the best furnace conditions. They are likewise useful in comparing operation of various furnace arrangements and to solve a number of other problems. However, sufficient data is not available on the reaction characteristics of natural fuel. Therefore, the nomograms were first used to determine the combustion constants from data obtained during heat balance tests on industrial furnaces. The mean flame temperature enters into the calculation and the determination of this temperature is next considered.

Card 3/7

SOV/96-58-11-6/21

An Approximate Method of Calculating the Combustion of a
Pulverised Fuel Flame

An empirical formula for the temperature change over the length of the flame is given. The position of maximum temperature under various conditions is discussed. Several methods have been proposed to determine the mean temperature but they are not sufficiently in accord with combustion conditions. An expression is given for the determination of the mean temperature. By successive numerical integration of one side of this expression with subsequent determination of the mean temperature, graphs were constructed for the mean temperature of the flame. These are given in Fig.5. Practical test data are then analysed. The method of calculation described above was used to work out test results on a number of industrial furnaces in order to determine the combustion-rate constants for cokes of natural fuels. It was assumed that the mean particle velocity is the same as the gas velocity and that particles do not re-circulate. Forty series of industrial tests, totalling about 600 sets of

Card 4/7

SOV/96-58-11-6/21

An Approximate Method of Calculating the Combustion of a
Pulverised Fuel Flame

results of tests on different types of furnace, were analysed. The fuels involved range from anthracite to lignite. The test data adequately covers the range of conditions encountered in industrial furnaces. The results are plotted in Fig.6. as the relationship between the logarithm of the apparent reaction-speed constant and the reciprocal of the absolute temperature. The values of the apparent kinetic combustion constants for any given fuel are grouped round a straight line with a maximum scatter of + 60% from the mean. Individual test results in which the burners were working irregularly are excluded. Provided combustion is normal, the values of the apparent constants for any given fuel are practically independent of burner construction and arrangement because in modern furnaces with long flames the initial mixing conditions influence only the stability of ignition. Because it was assumed

Card 5/7

SOV/96-58-11-6/21

An Approximate Method of Calculating the Combustion of a
Pulverised Fuel Flame

that the flame flows only forward the constants determined are not universally applicable but they can be used for combustion calculations on furnace chambers of the type here analysed. Further test data must be worked out for various industrial furnaces and rigs so that the influence of aerodynamic factors can be assessed and the values of more generally applicable constants determined. Comparison between the test data and laboratory data given in Fig.7. shows that in both cases the values of the constants are of the same order. Therefore, very extensive data obtained with different furnaces and different kinds of fuel have confirmed the general validity of the given method of analysing combustion. The accompanying methods of calculation, including the nomogram, can be used for quantitative evaluation of the behaviour of the combustion process under particular conditions in a given furnace. They can be used

Card 6/7

SOV/96-58-11-6/21

An Approximate Method of Calculating the Combustion of a
Pulverised Fuel Flame

to compare the operation of furnaces and to determine
the influence of various factors on the rate of fuel
consumption and also to compare different methods
of burning fuel. There are 7 figures, 1 table and
9 Soviet references.

ASSOCIATION: Tsentral'nyy kotloturbinnyy institut
(Central Boiler Turbine Institute)

Card 7/7

S/196/61/000/006/012/014
E194/E435

AUTHORS: Pomerantsev, V.V., Shagalova, S.L., Aref'yev, K.M.
TITLE: Analysis and calculation of the combustion of a pulverized fuel flame
PERIODICAL: Referativnyy zhurnal, Elektrotehnika i energetika, 1961, No.6, p.10, abstract 6G62. (Sb. 3-e Vses. soveshchaniye po teorii goreniya. T.2., M., 1960, pp.158-160)

TEXT: Existing procedures for calculating the combustion of coal dust have not been used in engineering practice. New efforts in this direction have been undertaken in the TsKTI (Central Boiler and Turbine Institute). The procedure is based on solving the problem of combustion of a pulverized fuel flame which is of uniform particle size distribution across the section. The solution allows for the combined influence on the process of kinetic and diffusion factors and also allows for varying concentration and approximately for the temperature distribution in the flame. The main assumptions are: (1) the speed and temperature of the fuel particles are assumed to be the same as those of the gas flow in which they are carried; (2) when the fuel is milled the ash is

Card 1/2

SHAGALOVA, S.L., kand.tekhn.nauk; AREF'YEV, K.M., inzh.

Analyzing the effects of operating conditions parameters
on the magnitude of mechanical underfiring in compartment
furnaces. Teploenergetika 7 no.2:41-47 P '60.

(MIRA 13:5)

1. TSentral'nyy kotloturbinnyy institut.
(Furnaces)